



Long Island Sound

FRAMES MARKED X OF DIMENSIONS  
 AT HEEL: 38x29 MM, AT HEAD: 30x29 MM  
 STEAMBENT OF OAK BETWEEN THESE FRAMES  
 2 BENT FRAMES OF OAK, ELM OR ASH 29x23 MM  
 REDUCED AT ENDS TO 25x21 MM  
 DECKBEAMS OF PINE  
 BEAMS MARKED 'A' 45x60 MM 45x45 MM  
 "B" 35x50 MM 35x40 MM  
 "C" 30x40 MM 30x40 MM  
 "D" 30x40 MM

12 MM OREGON PINE OR PLYWOOD  
 CANVAS COVERED  
 MANOGANY  
 DECK - NORWAY SPRUCE: 16 MM OR PLYWOOD EQW.  
 CANVAS COVERED  
 MANOGANY 18 MM  
 PINE 100 x 25 MM  
 RED AT ENDS TO 75x25  
 PRANKING - OREGON PINE OR MANOGANY EQW.  
 VERT. GRAINED 19 MM THICK  
 PLANKS GLUED TOGETHER.

FLOORING 15 MM PINE EQW.  
 MANOGANY 15 MM OR PLYWOOD EQW.  
 FLOORS OF OAK OR EQW SEE LONGITUDE PLAN  
 FASTENED TO FRAMES WITH 4 BRONZE BOLTS  
 LEAD KEEL  
 7/8" BOLTS BRONZE

INTERNATIONAL ONE DESIGN CLASS -  
 WORKING PLAN  
 SCALE 1:10 1/4  
 DESIGNER BJARNE AAS FREDRIKSTAD, NORWAY JUNE 1936

7500 J. ©

REVISED MARCH 1963

Richard J. de Boer